





NAV-CHR-515009B
High Neck Basin Mixer without Popup Waste with 450mm Long Braided Hoses
Braided hoses, 1/2" FIP (WRAS Approved) Withstand pressure of 10 Bar
5.12 LPM @ 3 bar
1.0 Bar - 5 Bar
Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) Copper Pipe as per IS:2501-1995
Cu (99.9%), Other elements (0.1%)
Cartridge with Brass Spindle Life Cycle EN 817: 70,000 cycles (Standard) - 2.1 LAC Cycles as per EN 817* - 10.5 LAC Cycles (ON/OFF)*
16 bar (Pass)
25 bar (Pass)
Plating: Nickel-13.0 micron Chromium-0.40 micron Salt Spray (600 hrs + Validated) Adhesion (Pass)
M24X1
Black Matt (BLM), Blush Gold Bright PVD (BGP), Black Pearl PVD (BLP) & Gold Bright PVD (GBP)

^{*} As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.