







Γ	
Product Code	NAV-CHR-515845BR False ceiling installation kit for Navia Rainjoy Shower 450mm consisting of 1 Bracket, 4 Anchors, 4 Stud bolts, 12 Hex nuts (Compatible with NAV-515845SH & NAV-515847SH)
Product Code	NAV-CHR-515845SH  Navia RAINJOY Shower 450mm AISI 304 stainless steel with RGB LED lights & remote control, without installation kit for false ceiling  • Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz  • 3-functions  • Rain, • Intense, • 4 X Mist
Flow Rate	Rain - 46.88 LPM @ 3 bar Intense - 23.98 LPM @ 3 bar Mist - 2.46 LPM @ 3 bar
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Ceiling Mounting
Spray Modes	Rain, Intense & Mist Functions
	Brass Rod as per IS:319-1989
	Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
Material Composition Specification in Percentage	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304)
	ABS:Specific Gravity (g/cm2) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102
REMOTE CONTROL	Automatic mode changing - next  Speed Down Park - fund to be good Among color - previous  Mong color - previous  Mong color - previous  Automatic mode changing - next  Speed Up Purk - fund to be good upon paramete mode Increase Brightness of LED  Automatic mode changing previous  HOW TO CHANGE BATTERY
LED POWER SUPPLY	CHROMO THERAPY (RGB)  LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz  COLOR VARIATION  Mono Color (RGB)  Chromo Theraphy  LED On / Off
Finish	Switch Sensor by Remote Control  Salt Spray (600 hrs + Validated)  Addressing (1994)
Available Finishing	Adhesion (Pass)  Black Matt (BLM), Blush Gold Bright PVD (BGP), Black Pearl PVD (BLP) & Gold Bright PVD (GBP)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites,	

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.