




Product Code	NAV-CHR-515027K
Description	Exposed Part Kit of Floor Mounted Basin Mixer (Compatible In-Floor part ALA-509027 is sold separately)
Flow Rate	5.85 LPM @ 3 bar
Recommended Water Pressure	1.0 Bar - 5 Bar
Material Composition Specification in Percentage	Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder) Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) Copper Pipe as per IS:2501-1995 Cu (99.9%), Other elements (0.1%)
Cartridge Specification	Cartridge with Brass Spindle Life Cycle EN 817: 70,000 cycles (Standard) - 2.1 LAC Cycles as per EN 817* - 10.5 LAC Cycles (ON/OFF)*
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Finish	Plating: Nickel-13.0 micron Chromium-0.40 micron Salt Spray (700 hrs + Validated) Adhesion (Pass)
Aerator Size	M24X1
Available Colour Finishing	Black Matt (BLM), Blush Gold Bright PVD (BGP), Black PVD (BLP) & Gold Bright PVD (GBP)

* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.