



| | |
|--|--|
| Product Code | NAV-CHR-515187CS |
| Description | 2-Hole Basin Mixer with Casted Spout without Popup Waste |
| Connection Size | Braided hoses, 1/2" FIP (WRAS Approved) Withstand pressure of 10 Bar |
| Flow Rate | 5.12 LPM @ 3 bar |
| Recommended Water Pressure | 1.0 Bar - 5 Bar |
| Material Composition Specification in Percentage | Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder) Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) S.S Sheets as per AISI : 304 Ni (8.0-11.0), Ch (18.0-20.0), Mn (0.0-0.2), Ca (0.0-0.08), Fe (Remainder) |
| Cartridge Specification | Cartridge with Brass Spindle Life Cycle EN 817: 70,000 cycles (Standard) - 2.1 LAC Cycles as per EN 817* - 10.5 LAC Cycles (ON/OFF)* |
| Water Tightness | 16 bar (Pass) |
| Pressure Resistance | 25 bar (Pass) |
| Finish | Plating: Nickel-13.0 micron Chromium-0.40 micron Salt Spray (700 hrs + Validated) Adhesion (Pass) |
| Aerator Size | M24X1 |
| Available Colour Finishing | Black Matt (BLM), Blush Gold Bright PVD (BGP), Black PVD (BLP) & Gold Bright PVD (GBP) |

* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.